



Internationaler Fachverband für BESA | ZVR Nr. 975047937  
Hauptstraße 1, A 4861 Kammer-Schörfling am Attersee | AUSTRIA  
Tel.: 0043 - (0)664-73152899 | E-MAIL: [info@ifvbesa.at](mailto:info@ifvbesa.at)

# BESA-expert opinion

## to Project P51 7.0

Bioenergetic system analysis within the  
framework of BESA-seal of approval  
of the effectiveness of the product

„Hi Energy Wand 3“

of the company IPC Europe UG

Mr. Heuser Norbert

in case of degenerative energy deficiency





Internationaler Fachverband für BESA | ZVR Nr. 975047937  
Hauptstraße 1, A 4861 Kammer-Schörfling am Attersee | AUSTRIA  
Tel.: 0043 - (0)664-73152899 | E- MAIL: [info@ifvbesa.at](mailto:info@ifvbesa.at)

## **Client:**

Company IPC Europe UG  
Mr. Norbert Heuser  
Schwarzwaldstraße 48  
D-77866 Rheinau

## **Project participants:**

**Projekc leader:** Wolfgang Hans Albrecht, President and scientific director of IFVBESA

**Test person:** Eva Krankl, vicepresident and deputy scientific director of IFVBESA

**Proband:** 3 anonymous subjects

**other participanta:** none

**Project location:** Location of IFVBESA (international professional association for bioenergetic system analysis), Mainstreet 1, A-4861 Kammer/Schörfling am Attersee

**Date:** 22.10.2020 until 12.11.2020

**Project duration:** 21 Days



## Table of content

	page
1. basics of the project creation	04
2. funding performance of the IFVBESA	05
2.1 Project description	
Test procedure	
3. general information - effects of the magnetic field	09
3.1 Effects of the magnetic field	
3.2 Systemic requirements	
3.3 Technical device performance	10
3.4 Measurement procedure	11
3.5 Experimental performance and interpretation	
4. expert opinion	12
4.1 Measurement significance of BESA tests	
4.1.1 Significance criteria	
4.1.2 Statistical data analysis	
4.2 Biological relevance of the measurement results and effects	14
5 Authorized summary	15

### Important notes

The client has the right to use this expert opinion. Irrespective of this, this expert opinion represents intellectual property of IFVBESA as the contractor. The contractor is entitled to use this expert opinion for other purposes, if this does not violate the client's data protection and duty of confidentiality. Apart from this, this expert opinion, with the exception of the "authorized abridged version", may not be changed or passed on in abridged form without the consent of the IFVBESA. The order for this project refers to bioenergetically measurable values and their interpretation according to the guidelines of BESA or the IFVBESA. The maintenance of the quality of the tested products as well as their regular control are the task and responsibility of the client. Investigation of the manufacture, mechanism of action or interpretations of the Client's products to third parties are not the responsibility or task of the Contractor. Video recordings may only be made with the permission of IFVBESA.



## 1. basics of the research project P60 1.0

The international association for bioenergetic system analysis was commissioned by Mr. Norbert Heuser to test the effect of the "Hi Energy Wand 3" by means of bioenergetic system analysis (BESA) or to prove its effect. The testing took place independently of the subjective sensation of the respective test persons.

### **Description of the test object "Hi Energy Wand 3" by Mr. Norbert Heuser:**

The "Hi Energy Wand 3" is a technology that can be used as needle-free acupuncture on the meridians, meridian end points, on the chakras or other areas of the body or skin. It emits a specific spectrum of light that activates meridian energy without contact. In this way, the technology of the "Hi Energy Wand 3" improves the overall water balance in the organism. This, in turn, strengthens and accelerates micro-blood circulation. In this way, the body's own self-healing and thus health should be promoted.

This technology is already successfully used in the following areas:

- to improve the quality of all beverages
- to improve the quality of all foods
- relieves pain after burns
- relieves pain after sunburn
- relieves pain after mosquito bites
- relieves pain after ant bites
- promotes healing and recovery of wounds
- energizes water within seconds
- energizes food within seconds
- generally increases strength and energy

### General information transfer

The information transfer takes place from the hyperspace of the test object to the hyperspace of biological objects (humans, animals, plants). From there the information reaches the reference space or the energy space via so-called interaction channels. This is a union of, among other things, all organs and energy forms in the biological object. There, the information of the program can dynamically materialize and thus change current states. The changes can appear in the form of energization or neutralization of disturbances, dissolution of problems, blockages and disharmonies.

## 2. research support services of the IFVBESA - BESA- reference tests.

The project P51 7.0 dealt specifically with the proof of effect of the "Hi Energy Wand 3" in the environment of disturbances in the regulatory mechanism on the level of the body or



meridian energy. **IMPORTANT:** These disturbances can present themselves as traumas or imprints in the consciousness or in the energy channels of the meridians, at relevant acupuncture points of related organs, or show up in other areas on the body and skin. It should be checked whether the "test object" can neutralize the negative perception of the perceived disturbances on the organism.

The test object was tested according to the request of the client within the framework of the valid conditions of the IFVBESA for the award of quality seals. Basically, seals of approval are awarded in three categories depending on the significance of the test results, taking into account all the tests of a project.

For the "Hi Energy Wand 3" it was to be determined whether already indicated stresses in the energy system of the test person (biological system) can be neutralized by its application and thus negative pathological states can be replaced by positive states. This was questioned in the following commissioned tests of this project.

- what influence does the light of the "Hi Energy Wand 3" have on the human energy system and subsequently on the metabolism of the test person?
- what influence does the light of the "Hi Energy Wand 3" have on food and on drinking water
- what influence does the light of the "Hi Energy Wand 3" have on incriminating beliefs or imprints.
- Is the light of the "Hi Energy Wand 3", which was recorded via the camera of a smartphone (brand Samsung S20) for 30 seconds, able to have a regulatory effect on the organism of the test person, which might be burdened by the electromagnetic interference fields, by reproducing it as a viewed video?

## 2.1 Research project description:

The reason for the test was to prove the functionality of the "test object" by test results obtained by confronting subjects with precisely selected objects in order to significantly prove and compare their reactions without the "Hi Energy Wand 3" and with the "Hi Energy Wand 3". Subjects were contacted in one or more BEFORE measurements and the AFTER measurement, i.e., they were connected.

- The BEFORE measurements were made without the "Hi Energy Wand 3"
- The AFTER measurement was done with the "Hi Energy Wand 3"

The question for each AFTER measurement was: Is the "test object" suitable and able to neutralize the negative effects on the organism perceived in this way?



The correspondingly designed tests were to provide information about this by comparing the preliminary measurements without the "test object" with the test results of the post measurements carried out using the "test object".

The concern of the development team around Mr. Norbert Heuser was to have it determined whether the "test object" as noted in the product description is suitable to neutralize the regulatory disturbances or blockages in the meridian system of biological objects (test persons).

### **Conditions:**

The BESA tests were performed in the premises of IFVBESA under laboratory conditions, at room temperature 20°Celsius, on natural wood floor. The test persons were deswitched (made testable) before the BESA tests or the test possibilities were questioned with the respective test person.

- Pos.1** BESA 1 Testing Basic (bioenergetic status) on the test person
- Pos.2** BESA 2 Testing BEFORE of food and drinking water of the house tap water system on the test person
- Pos.3** BESA 3 Testing BEFORE after confrontation of the proband with active beliefs
- Pos.4** BESA 4 Testing AFTER confrontation of the test person with the listed stress factors with simultaneous application of the "test object" on the test person
- Pos.5** BESA 5 Testing AFTER confrontation of the test person with the light of the test object previously filmed on the smartphone.
- Pos.5** Evaluation of the results as well as summary in a corresponding expert opinion according to the sample.

### **Procedure and specifications for the implementation**

1. **BESA baseline measurement of the test persons** at all previously determined measurement points (TING points) serve to determine the actual condition. The results were determined exactly according to the BESA specifications and documented via the BESA graphs.
2. **the test persons** were brought **into contact with the stress factors depending** on the project, whereby the sequence discussed with Mr. Norbert Heuser was considered as a specification and was adhered to accordingly. In order to be able to determine the current energy state, the measuring points mentioned under point 1 were measured in the same order and for the same duration during each test. The results were determined exactly according to the BESA specifications and documented via the BESA graphs.
3. **Activation of the test object**



- 3.1. When the **"test object" was activated**, it was applied to the subject according to the client's instructions..
- 3.2. The test subjects were brought into contact with the stress factors. The measuring points mentioned in point 1 were measured in the same order and for the same duration in order to determine the current energy state. The results were determined exactly according to the BESA specifications and documented via the BESA graphs..

### 3. General information on BESA testing

#### 3.1 Effects of the magnetic field

The human being is a kind of receiving antenna for environmental information. This is because human life depends fundamentally and exclusively on environmental information. Our organism is biologically very sensitive where natural information (fields) is located or where this natural information is subject to interactions and fluctuations. **For this reason, detected informative interference fields are biologically highly relevant. Any reduction or transformation of these disturbances (ideally to 100 percent) is biologically very important, often even vital.** These informational disturbances from our environment are only compatible with life if they can be readjusted to a natural fluctuation tolerance. Disturbances, problems, blockades, disharmonies in the biological control circuit of the human being find their causes in such disturbing information influences. Bioenergetic examinations in the meridian system of the human being therefore belong to the first choice when it comes to questioning the coherent effectiveness of, for example, products in relation to various disturbing fields and information.

#### 3.2 Systemic requirements

The tests are carried out according to the specifications of the international professional association for BESA or the manual for BESA. BESA is used from a systemic, etiological and bioenergetic regulatory point of view. Systemic means that each tested parameter also represents several lower or higher levels and dimensions. Testing on a meridian, such as the lung meridian, primarily provides information about the energetic regulatory behavior within that meridian. In a subordinate sense, the readings of this meridian can provide information about the organic, muscular and emotional levels. In a superordinate sense, dimensions such as the astral plane (4th dimension) and various levels of consciousness (from the 5th dimension). Subsequently, the behavior in the structural, energetic, spiritual, craniosacral structure or dimension is also revealed. The bioenergetic measurements are made by stimulating the energetic potential within the meridians. Measurement voltages



average 900 to 1400 mV (millivolts) with a measurement current between 5.5 and 11.25  $\mu$ A (microamps). The apparent ohmic resistance varies during the measurement process between 0 and 600 k $\Omega$  (kiloohm) depending on the instantaneous, energetic state of the person being measured.

### 3.3 Technische Geräteleistung

Appropriate technical instrument performance ensures that not only skin resistance is measured during the measurement process, but also the interaction of various factors essential for the regulation of a system. From a physiological point of view, these include ionic current changes in the subcutaneous tissue, electrical potential against the measuring current, instantaneous polarization behavior of the tissue and electrolyte shifts. In addition to the electrophysical tissue properties in the area of the measuring point, the measurement should above all provide information about the regulatory capacity of the control circuit belonging to the measuring point.

Measuring device used: BESA Easy Quick- Check

SN: E 02074N

Labor Silberbauer; 1030 Vienna – Austria, battery: 2xNiMH Größe AA; 2,6V, 300mA max.

**Measurement tolerances:** In principle, fluctuations in measured values can occur, since the machine is operated by people who could specifically have an energetic influence on the measurement results. It is currently the case that only special experts, who have been further trained by the BESA Academy, carry out such tests. The current BESA tests were personally conducted or performed by Mrs. Eva Krankl as vice president and deputy head of the scientific department of IFVBESA. Certain quality details already programmed in the BESA software provide additional information about when a measurement result deviates from the programmed standards or when a measurement error has occurred by the tester. Another quality feature of BESA testing is that, as a precautionary measure against bias, each specialist must undergo an external examination for the tests. Insofar as the tests of technical (interference) fields show incriminating measurement results, occasional measurement errors of 10 percent could be ignored for such projects. However, experience shows that devices for harmonization of technical interference fields work or they do not work. As a matter of principle, IFVBESA applies the very highest precision according to precisely defined standards in BESA testing. These standards can only be met by professionals with 1000-fold diagnostic experience. Apart from this, electromagnetic (interference) fields acting from outside and possibly influencing the measurement results can be detected by device technology and corrected accordingly.

### 3.4 Measuring procedure:





BESA measurements are performed on "electromagnetically significant" points of the skin. These are partly classical acupuncture points as well as a number of energetically relevant and system-coupled skin areas. By electrophysical measurements at anatomically exactly localized skin areas the acquisition of the measurement data takes place:

- the current energetic state in the acupuncture point of the respective meridian
- the energetic regulation dynamics in the acupuncture point or meridian and its subordinate and superordinate systems and subsystems. This concerns the organ area (subordinate level) as well as the superordinate levels and dimensions of the morphic field of the human organism.

For simplified reading, the scale of BESA is divided into 100 graduation marks, where the scale reading "0 graduation marks" corresponds to a resistance above 600 kilohms and the scale reading "100 graduation marks" corresponds to a resistance of 0 ohms. The scale reading "50 graduation marks" represents 95 kilohms.

The experience of repeated measurements on healthy persons, carried out in decades, has shown that the value "50 scale divisions (sct.)" is a physiologically neutral (healthy) reference point. It is "the" outstanding and desirable measurement value and is also called the technical ZERO value.

**About the acupuncture point:** The anatomical structure of an acupuncture point is formed by a bundle of nerve vessels wrapped in loose connective tissue. Directly at the acupuncture point it pierces the superficial body fascia (Facia corporis superficialis = Fcs). Exactly at this point, the electrical resistance is also lower. Where no Fcs is developed (e.g. in the face, in parts of the head or at the end of the extremities), such a bundle of nerve vessels can also be detected in the acupuncture point. This also applies to the special conditions along the DuMai meridian (governor or steering vessel at the front of the body) and the RenMai meridian (conception vessel at the back of the body). There, in the point area, the nerve vessel bundles of both sides of the body are interconnected.

### 3.5 Experimental performance and interpretation

The obtained measurement signals at the acupuncture points of the meridians are an expression of the energetic events and the energetic regulation ability of the obtained environmental signals. The presented BESA standard graphics (see the detailed project descriptions) show the respective energetic regulation behavior within the indicated meridians. The meridians belonging together in each case are represented in so-called form circles or elements. A distinction is always made between the right and the left side. In order to obtain the most differentiated illustration possible, degenerative measured values (energy deficiency) are shown in blue and overheated or inflammatory measured values (energy surplus) in yellow. Optimal measured values are shown in green (50 to 70 sct.), whereby the measured value 50 sct. is to be aimed at, because it represents a balanced regulatory behavior. Readings that show up in red indicate a deeper deregulation that



currently cannot be regulated by the organism. The effect of the tested product on the field or the differences of the regulatory behavior in the organism are mapped or documented by differentiated measurements on the respective BESA measurement data sheets marked for this purpose. (see project description P51 7.0)

## Interpretation of BESA measurement results

**The measured value of 50 on the tested meridian represents an optimal energetic state in this organ or its higher levels.**

**Also measured values in the range of 50 to max. 70 still count as a neutral and balanced energy status. The organism is able to regulate irritations of the system (wrong environmental signals) very well.**

Readings above 70 to 100 represent the inflammatory range or a so-called energy surplus in response to the irritation of the system by environmental signals corresponding to it.

After reaching the maximum values, the energy state tilts into the degenerative (blue) range.

Readings from below 50 to near 0 represent the so-called degenerative measurement range or a lack of energy in response to the stimulation of the system by environmental signals corresponding to it.

**Measured values represented by a so-called pointer drop of more than 3 scale lines indicate a total deregulation.**

**The influence of certain environmental signals then leads to such strong system overloads, which can only be harmonized by corresponding new signals.**

## 4. 4. expert opinion

The measurement results presented in the project description P51 7.0 have shown that after application of the test object, the "Hi Energy Wand 3", all previously stress-tested information and energetic deregulations could be zeroed and bioenergetically harmonized within the specified time frame. The graphical evaluations of the BESA tests document the results in a qualitatively comprehensible way through the color-coded measured values. The measured values highlighted in green in the graphic evaluations show as quantitative effects a consistently balanced bioenergetic regulation in the meridians and thus in all subordinate and superordinate levels and dimensions.

*The expert opinion thus confirms the quantitative results in that they are as follows: 1. metrologically significant (meaningful) and 2. biologically relevant (important or significant).*

### 4.1 Metrological significance of the BESA tests



#### **4.1.1 Significance Criteria:**

**The effects determined in the BESA tests** as a result of the bioenergetic resonance behavior, show both in the area of status determination (effect from the area of existing interference fields by various toxic substances or environmental information and the resulting bioenergetic interference fields or subsequently arising body-immanent deregularities) and after application of the test object changes that are clearly above the specified measurement tolerances. Thus, they are clearly to be classified as **significant**. According to the criteria of the IFVBESA, all those measurement results are considered significant that allow regulation into the green range.

According to the criteria of the IFVBESA, the BESA measurement values are to be regarded as reliable. That the criteria for the established results are fulfilled could be proven via the BESA tests in the project P51 7.0.

#### **4.1.2 Statistical data analysis**

Each series of measurements can have measurement points where effects remain below the significance threshold (transition areas). A statistical analysis has the advantage of presenting an overall view of the significance of the effects. Exactly these effects are obtained for seals of approval with 4 or 5 stars. The more extensive the data, the more accurate the statistical analysis.

In the BESA tables and graphs, the statistical characteristics of currently 440 measured values and results were mapped. As can be seen from the statistical data and the BESA graphs, the measured values improved significantly between the BESA pre-measurements and BESA post-measurements. The effects achieved by the test object were confirmed by the BESA measurements on the nine test subjects.

#### **4.2 Biological relevance (importance) of measurement results and effects**

In case of continuous exposure of humans to toxic information (as presented in the project P51 7.0) or toxic stress factors, the exposure becomes all the more severe. This is shown by the currently performed BESA tests on the test persons. In any case, these and similar stress factors represent a serious risk for human salutogenesis.

The test object bioenergetically checked in this project, the "Hi Energy Wand 3" of the company IPC Europe UG - by Mr. Heuser Norbert could neutralize the bioenergetically stressing effects and impacts.

***The significant ability of the "Hi Energy Wand 3" to harmonize the toxic stress factors from the environment of the test persons tested in the project P51 7.0, respectively the transformation into biological information of life-promoting quality is proven by this expert opinion.***



## 5. Authorized Summary:

The BESA tests conducted by IFVBESA on the energetic and physical effectiveness of the "Hi Energy Wand 3" have clearly shown that it is capable of energizing and thus balancing (neutralizing) biologically significant stress factors in the meridians or at the acupuncture points of the test persons. By means of the bioenergetic system analysis, the effect of the above-mentioned stress factors on the test persons, their meridian systems and their energetic-biological control circuits was scrutinized and systemically tested on the energetic level. The BESA tests BEFORE - AFTER show significant changes at the tested acupuncture points at the meridian system of the test persons. The measured data as well as their key figures impressively confirm, on the one hand, the stresses that occur on the human organism and, on the other hand, clarify how, after application of the "Hi Energy Wand 3", the deregulating energies are transformed into body-immanent and biocompatible energies.

From a holistic point of view, it may be assumed that the positive effect on the test persons also occurs in other people. That the positive influence by the "Hi Energy Wand 3" is actually possible with high precision is clearly shown by this test through the BESA-PRE-AFTER-AFTER comparison. All measured values improved significantly from the mostly 100-percent blue measuring range into the green mostly 50-second range (scale value), i.e. the range of optimal measured values. This means that an optimal regulation dynamic has taken place. Here, in the sense of IFVBESA, one can clearly speak of an optimal, significant improvement of the body's own energy situation.

### Result

The test persons were brought into contact with stressed objects during the BESA-NACHHER test. In contrast to the BEFORE tests, in which the "Hi Energy Wand 3" was not used, positive measurement results were found throughout, indicating that energization (neutralization) had taken place. The regulation dynamics developed into an optimal effective range..

By demonstrating the energy efficiency of the "Hi Energy Wand 3" in this P51 7.0 project, the requirements for obtaining a BESA 5-star seal of approval from the International Professional Association for BESA were met.